



PrestiVac™

VACUUM MODEL AV1-10 EX RCT AIR OPERATED EXPLOSION PROOF VACUUM

- ☐ POWERFUL SUCTION – HIGH PERFORMANCE
- ☐ 200" H₂O / 120 CFM
- ☐ STAINLESS STEEL
- ☐ HEPA^{Plus*} FILTRATION 99.995 % @ 0.2 MICRON
- ☐ STATIC DISSIPATING ESD SAFE
- ☐ RCT REMOVABLE COLLECTION TANK
- ☐ 3 YEAR WARRANTY



Explosion Proof / Dust Ignition Proof Compressed Picture shown is for illustration purpose only. Actual product may vary.

Air-Operated Pneumatic Industrial Vacuums

PrestiVac explosion proof/dust ignition proof vacuums are specifically designed to safely vacuum explosive, flammable, combustible dusts. Our explosion proof/dust ignition proof vacuums are completely grounded and static dissipating because they are built entirely with non-sparking metals and do not have any painted components so there is no risk of fire or explosion from a spark or static build up. Compressed Air-Operated Vacuums do not have any electrical components that can overheat and be a source of ignition. Our explosion proof/dust ignition proof vacuums comply with NFPA 484 guidelines and are an effective tool for good housekeeping practice as per OSHA.

II 2 GD c IIC T6 (85°C)

Class I, Division 1, Groups A, B, C, and D T6 and Class II, Division 1, Groups E, F, G Hazardous Locations as defined in the National Electric Code (NEC) and NFPA 70
EPL Db and EPL Gb (Equipment Protection Level)



PrestiVac™

Features:

- Powerful Suction – High Performance
- Stainless steel construction makes it a solid unit that is easy to clean
- Automatic Filter Shaker
- Static dissipating ESD safe
- Complete with static dissipating suction hose and accessories
- RCT Removable Collection Tank system makes it easy to empty and clean
- Stainless steel storage bin for hose and accessories
- Quiet operation with only 72 dB



Filtration System:

- Washable Conductive ESD safe filters
- HEPA^{Plus*} Filtration with an efficiency of 99.995% @ 0.2 micron

Specifications:

- 200" H₂O Vacuum Pressure
- 120 CFM
- Dry Collection Only
- Collection Capacity 10 gallons (44L)

Air requirements:

- 35-50 CFM Input Air Flow
- 90 to 100 PSI Input Pressure
- ½" Air Line Hose



Included Accessories:

- Static Dissipating Air Line hose 0.5" x 25'
- Static Dissipating suction hose assembly 1.5" x 10'
- Crevice tool ESD safe
- Round brush ESD safe
- Double Bend Wand ESD safe
- Floor Tool ESD safe

□

