



PrestiVac™

VACUUM MODEL AV1-5 EX HEPA AIR OPERATED EXPLOSION PROOF VACUUM

- ☐ POWERFUL SUCTION – HIGH PERFORMANCE
200'' H₂O / 120 CFM
- ☐ STAINLESS STEEL
- ☐ STATIC DISSIPATING ESD SAFE
- ☐ 4 WHEEL CART
- ☐ 3 YEAR WARRANTY
- ☐ HEPA^{Plus*} FILTRATION 99.995 % @ 0.2 MICRON



Explosion Proof / Dust Ignition Proof Compressed Air-Operated Pneumatic Industrial Vacuums

Picture shown is for illustration purpose only. Actual product may

vary.

PrestiVac explosion proof/dust ignition proof vacuums are specifically designed to safely vacuum explosive, flammable, combustible dusts. Our explosion proof/dust ignition proof vacuums are completely grounded and static dissipating because they are built entirely with non-sparking metals and do not have any painted components so there is no risk of fire or explosion from a spark or static build up. Compressed Air-Operated Vacuums do not have any electrical components that can overheat and be a source of ignition. Our explosion proof/dust ignition proof vacuums comply with NFPA 484 guidelines and are an effective tool for good housekeeping practise as per OSHA.

Absolute HEPA^{Plus*} filtration with an efficiency of 99.995% @ 0.2 micron captures all the hazardous dust and ensures the exhaust air is clean, keeping the operator and the environment safe from exposure and contamination

II 2 GD c IIC T6 (85°C)

Class I, Division 1, Groups A, B, C, and D T6 and Class II, Division 1, Groups E, F, G Hazardous Locations as defined in the National Electric Code (NEC) and NFPA 70

Certified EPL Db and EPL Gb (Equipment Protection Level)



PrestiVac™

Features:

- Powerful Suction – High Performance
- Stainless steel construction makes it a solid unit that is easy to clean
- Static dissipating ESD safe
- Complete with static dissipating suction hose
- Quiet operation with only 72 dB

Filtration System:

- Washable Conductive ESD safe filters
- HEPA^{Plus*} Filtration with an efficiency of 99.995% @ 0.2 micron.

Specifications:

- 200" H₂O Vacuum Pressure
- 120 CFM
- Dry Collection
- Collection Capacity 5 gallons

Air requirements:

- 35 to 50 CFM Input Air Flow
- 80 to 100 PSI Input Pressure
- ½" Air Line Hose

Included Accessories:

- Static Dissipating Air Line hose 0.5" X 25'
- Static Dissipating suction hose assembly 1.5" x 10'
- Wand 1.5" Pull Pin Type
- Floor Tool 1.5"
- Crevice tool
- Round brush

